



PARTS LIST				
PART NO.	DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1S	2-1S	TOP	CAST IRON	1
2	26-2A	FLANGE	CAST IRON	1
3	26-3AL	BODY	CAST IRON	1
4	26-4S	A & V FULCRUM	STAINLESS STEEL	1
6	26-6S	VALVE LEVER	STAINLESS STEEL	1
7	13-7R	LINK	STAINLESS STEEL	2
8	26-8R	BALL LEVER	STAINLESS STEEL	1
9	26-9R	FLOAT	STAINLESS STEEL	1
10	26-10AS	BALL FULCRUM	STAINLESS STEEL	1
11	13-4N	VALVE PLUNGER	BUNA-N & S/S	1
12	13-3N	PLUNGER NUT	STAINLESS STEEL	1
13	13-3W	LOCK WASHER	STAINLESS STEEL	1
15	26-15	PRESSURE SEAT	STAINLESS STEEL	1
16	26-5-16S	PRESSURE FULCRUM	STAINLESS STEEL	1
17	26-17S	SEAT CAGE	STAINLESS STEEL	1
18	2-5	SEAT	BUNA-N RUBBER	1
23	13-12R	BEARING PIN	STAINLESS STEEL	1
23A	26-11S	BEARING PIN	STAINLESS STEEL	1
24	13-11R	BEARING PIN	STAINLESS STEEL	2
25	13-11AR	BEARING PIN	STAINLESS STEEL	2
26	18-7A	COTTER PIN	STAINLESS STEEL	6
29	27-29	PLUG (FLANGE)	BRASS	1
29A	PLG-.5	1/2" PLUG (BODY)	BRASS	1
30	13-26	FULCRUM WASHER	FIBER	2
32	13-24	FLANGE GASKET	ARMSTRONG	1
33	2-15	BOLT	STEEL	7
34	2-12	NUT	STEEL	9

ORIFICE DATA	
DIAMETER	MAX. WORKING PRESSURE
3/16"	150 PSIG
3/32"	300 PSIG

**NOTES:**

1. INLET SIZE: 1" NPT; OUTLET SIZE: 1" NPT.
2. APPROXIMATE WEIGHT: 27 lbs.
3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 2-5 AND 13-4N TO SOFT SEATING MATERIAL 2-5L AND 13-4NL.
4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 2-5 AND 13-4N TO HARD SEATING MATERIAL 2-5H AND 28-4N.

DO NOT SCALE DRAWINGS ALL DIMENSIONS ARE IN INCHES		<b>Crispin Valves</b>	
		<b>1" COMBINATION AIR RELEASE VALVE (UNIVERSAL TYPE)</b>	
REDRAWN:	DATE:	SIZE C	DWG NO. UL10
CHECKED: BJL	9-6-13	REV 0	
DRAWN: DJF	9-6-13	SCALE 1.00 = 1.00	ASSEMBLY DRAWING SHEET 1 OF 1

REV	DESCRIPTION	DATE	APPROVED
REVISIONS			