



UNIVERSAL SEWER VALVE PARTS LIST

ITEM	DWG. NO.	DESCRIPTION	MATERIAL	QTY.
1S	2-1S	TOP	CAST IRON	1
2	36-U2-2/1	FLANGE	CAST IRON	1
3	36-21-2SL	BODY, SCREWED	CAST IRON	1
3W	13-3W	LOCKWASHER	STAINLESS STEEL	1
4	26-4S	AIR/VACUUM FULCRUM	STAINLESS STEEL	1
6	26-6S	VALVE LEVER	STAINLESS STEEL	1
7	13-7R	LINK	STAINLESS STEEL	2
8	36-U2-10	BALL LEVER	STAINLESS STEEL	1
9	36-U2S-9	FLOAT	STAINLESS STEEL	1
9A	27-9A	FLOAT ROD	STAINLESS STEEL	1
10	26-10AS	BALL FULCRUM	STAINLESS STEEL	1
11	13-4N	PLUNGER	BUNA-N RUBBER & S/S	1
12	13-3N	PLUNGER NUT	STAINLESS STEEL	1
15	26-15	PRESSURE SEAT	STAINLESS STEEL	1
16	26-5-16S	PRESSURE FULCRUM	STAINLESS STEEL	1
17	26-17S	SEAT CAGE	STAINLESS STEEL	1
18	2-5	AIR/VACUUM SEAT	BUNA-N RUBBER	1
23	13-12R	BEARING PIN	STAINLESS STEEL	1
23A	26-11S	BEARING PIN	STAINLESS STEEL	1
24	13-11R	BEARING PIN	STAINLESS STEEL	2
25	13-11AR	BEARING PIN	STAINLESS STEEL	2
26	18-7A	COTTER PIN	STAINLESS STEEL	6
30	13-26	FULCRUM WASHER	FIBRE	2
32	14-24	FLANGE GASKET	ARMSTRONG	1
33	3-11	FLANGE BOLT	STEEL	7
34	3-12	NUT	STEEL	7
36	2-12	FULCRUM NUT	STEEL	2

BACK FLUSH PARTS LIST

1B	HA 1" X 5'	HOSE ASSEMBLY	S/S, CAD PLY, RUBBER	1
2B	NPL 1" X 3'	NIPPLE	STEEL	1
3B	NPL 1" X 3'	NIPPLE	STEEL	1
4B	NPL 2" X 3'	NIPPLE	STEEL	1
5B	BV-1	1" BALL VALVE	BRASS	2
6B	BV-2	2" BALL VALVE	BRASS	1

NOTES:

1. INLET SIZE: 2" NPT; OUTLET SIZE: 1" NPT.
2. APPROXIMATE WEIGHT - 60 lbs.
3. WHEN OPERATING PRESSURE IS BELOW 20 psig, REPLACE ITEM NO. 2-5 AND 13-4N TO SOFT SEATING MATERIAL 2-5L AND 15-4N.
4. WHEN OPERATING PRESSURE IS ABOVE 150 psig, REPLACE ITEM NO. 2-5 AND 13-4N TO HARD SEATING MATERIAL 2-5H AND 28-4N.
5. OVERALL HEIGHT: 16.38 in.
OVERALL WIDTH: 13.56 in.

DO NOT SCALE DRAWING DIMENSIONS ARE IN INCHES		Crispin Air Valves	
		2" INLET 1" OUTLET "SHORT BODY" UNIVERSAL SEWER VALVE	
REDRAWN: AJM	DATE: 03/07/96	DWG. NO. US10SB	REV 1
CHECKED: BJL	DATE: 03/07/96	SCALE: 0.75 = 1.0	SHEET 1 OF 1
DRAWN: LAD	DATE: 03/10/88		

REV	DESCRIPTION	DATE	APPROVED
A	CHG'D PART NUMBER 18 FROM 2-5 TO 2-5L	12-17-04	BJL
REVISIONS			